

Available as safety goggles or as a complete shield using its face screen, VUETIX™ seals and protects the eyes to offer a lightweight and extremely comfortable wearing experience. It offers an excellent pressure-free fit and when worn with the accompanying shield, additional face protection against liquid splashes and airborne particles is provided.

## SPECIAL FEATURES

- ✓ Wide field of vision
- ✓ Padded face seal
- ✓ Strong polycarbonate lens
- ✓ Soft PVC/TPE frame and comfort nose bridge
- ✓ Adjustable elasticated head strap
- ✓ Molten metal splash protection (goggle only)
- ✓ Can be worn over a prescription frame
- ✓ Available with optional face protector
- ✓ Weight: 123g (Goggle), 70g (Face Protector)



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	RLY00181	2C-1.2 e 1BT9 CE	e EN166 349BT CE	Impacts, Liquid Droplets, Molten Metal, Airborne Particles	Standard Anti-fog
FACE PROTECTOR	RLY00182	2C-1.2 e 1BT CE	N/A	Impacts, Liquid Droplets	

See overleaf for this product's technical specification

## GENERAL SPECIFICATION

LENS BASE	5mm
WEIGHT	123g (+70g Face Protector)

## PACKAGING

Goggles are individually contained in a polythene bag with a Euroslot. Face protectors packaged separately.

PER BOX	5
PER CARTON	100

## COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Single piece
FRAME	Polycarbonate, PVC, Thermoplastic Elastomers (TPE)	Durable and comfortable
HEAD BAND	Woven Elastic	Adjustable
FACE PROTECTOR	Polycarbonate	Ventilated

## LENS MARKINGS

### LENS FILTER TYPE:

2C UV

### SCALE NUMBER (SHADE):

1.2 Clear or Amber

 Identity of the manufacturer

### OPTICAL CLASS:

1 High optical quality

### MECHANICAL STRENGTH:

- B** Medium energy impact, resists a 6mm, 0.86g ball at 120m/s
- T** Protection against high-speed particles at extreme temperatures
- 9** Molten metal splash

 Certification mark

## FRAME MARKINGS

 Identity of the manufacturer

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

### FIELDS OF USE:

- 3** Liquid droplets or splashes
- 4** Large dust particles > 5 µm
- 9** Molten metal and hot solids

### MECHANICAL STRENGTH:

- B** Medium energy impact, resists a 6mm, 0.86g ball at 120m/s
- T** Protection against high-speed particles at extreme temperatures

 Certification mark

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

## PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

[www.riley-eyewear.com](http://www.riley-eyewear.com)

E: [info@riley-eyewear.com](mailto:info@riley-eyewear.com)

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

