



Custom designed optic with optional, interchangeable Smoke-Cutter® plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare

Case: Housing, base and battery housing made from high impact super tough nylon offering exceptional durability. All openings are O-ring sealed for weather resistance.
Material: Spring loaded clip with built in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One way valve for case venting. Available in international safety orange, high visibility yellow or black

Dimensions/ Height: 7.06 in. (17.92 cm); Height in charger: 8.67 in. (22.02 cm); Width: 2.85 in. (7.24 cm); Diameter: 2.87 in. (7.29 cm) Grip area: Height: 3.6 in. (9.14 cm); Thickness: 1.35 in. (3.43cm); Width: 2.20 in. (5.59 cm)

Weight: NiCd: 18.0 oz (510 grams) Alkaline: 13.7 oz (388 grams)

Light: C4® LED technology, impervious to shock with a 50,000 hour lifetime

Source: Custom "Total Internal Reflection" optic for narrow beam and optimum peripheral illumination. Insertable black plug reduces peripheral illumination for improved smoke cutting ability or amber plug reduces eye fatigue.

Four lighting modes:

- High for a super-bright beam that pierces through smoke: 41,000 candela; 175 lumens; 405m beam distance; runs 3.5 hours (NiCd); runs 4 hours (alkaline)
- Low for bright light and longer run time: 14,000 candela; 60 lumens; 237m beam distance; runs 13 hours (NiCd); runs 15 hours (alkaline)
- Flash for signaling: runs 8 hours
- Moonlight mode provides low-level lighting for battery conservation: runs 20 days

On/Off: Ultrasonic welded push button switch designed for extremely long life. Rubber dome push button actuator provides easy operation even when wearing heavy gloves.

Battery: Industrial rechargeable nickel-cadmium 4.8 volt, 1.8 amp hour, 4 cell sub-C rechargeable up to 1,000 times. Optional four "AA" alkaline battery pack provides fast replacement with readily available batteries.

Charging: AC and DC one-hour fast chargers with full charge indicators designed specifically for AC or DC power sources. Universal steady charger requires up to 10 hours for a complete charge, can be used with AC or 12V DC by exchanging its charge cord

Features:

- Reduced bezel length to minimize snag hazards
- Updated clip design for easy attachment on turnout gear
- IPX4 rated design; water resistant
- 2 meter impact resistance tested.

Approvals: Class I, II, Division 1, Groups C, D, E, F, G; Class III, T-Code: T4
 Class I, Division 2, Groups A, B, C, D; T-Code: T4

Charger meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position

MSHA: Permissible Flashlight, Approval No. 20-A150001-0.

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction

Item Description	UPC Code	Item #
Survivor - IEC Type C (230V) AC/12V DC - Yellow (NiCd)	080926-90515-3	90515
Survivor - IEC Type A (120V) AC/12V DC Smart Charge - Yellow (NiCd)	080926-90513-9	90513
Survivor - IEC Type C (230V) AC/12V DC - Orange (NiCd)	080926-90505-4	90505
Survivor - IEC Type A (120V) AC/12V DC Smart Charge - Orange (NiCd)	080926-90503-0	90503
Survivor - IEC Type C (230V) AC/12V DC - Black (NiCd)	080926-90525-2	90525
Survivor - IEC Type A (120V) AC/12V DC Smart Charge - Black (NiCd)	080926-90523-8	90523
Survivor - IEC Type A (120V) AC Fast Charge - Yellow (NiCd)	080926-90512-2	90512
Survivor - IEC Type A (120V) AC Fast Charge - Orange (NiCd)	080926-90502-3	90502
Survivor - IEC Type A (120V) AC Fast Charge - Black (NiCd)	080926-90522-1	90522

Item Description	UPC Code	Item #
Survivor - 12V DC - Yellow Fast Charge (NiCd)	080926-90519-1	90519
Survivor - 12V DC Fast Charge - Black (NiCd)	080926-90528-3	90528
Survivor - 12V DC Fast Charge - Orange (NiCd)	080926-90509-2	90509
Survivor - (WITHOUT CHARGER) - Yellow (NiCd)	080926-90510-8	90510
Survivor - (WITHOUT CHARGER) - Orange (NiCd)	080926-90500-9	90500
Survivor - (WITHOUT CHARGER) - Black (NiCd)	080926-90520-7	90520
Survivor Alkaline Model - Yellow	080926-90541-2	90541
Survivor Alkaline Model - Orange	080926-90540-5	90540
Survivor Alkaline Model - Black	080926-90545-0	90545



DESCRIPTION	UPC	ITEM #
DC2 direct wire charge cord (All Rechargeables)	080926-22050-8	22050
DC1 Charge Cord (All Rechargeables)	080926-22051-5	22051
IEC Type A AC Plug (100V/120V)	080926-22060-7	22060
IEC Type C AC Plug (230V)	080926-22061-4	22061
IEC Type G AC Plug (240V)	080926-22062-1	22062
Steady Charge (SC) Plug-In Charger Holder (Knucklehead/Survivor LED)	080926-90010-3	90010
Smart Charge (SC) Plug-In Charger Holder (Knucklehead/Survivor LED)	080926-90116-2	90116
Fast Charger Holder (Knucklehead/Survivor LED)*	080926-90011-0	90011
DC #1 Fast Charger (Knucklehead/Survivor LED)*	080926-90012-7	90012
DC #2 Fast Charger (Knucklehead/Survivor LED)*	080926-90013-4	90013
NiCd Battery Pack (Blue Sleeve) (Survivor, also works with Knucklehead) (not for sale in EU)	080926-90130-8	90130
NiCd Battery (Orange Sleeve) (Survivor/Khead HAZ-LO) (not for sale in EU)	080926-90335-7	90335
NiCd Battery (Black Sleeve) (Incandescent Survivor Div 2, Knucklehead) (not for sale in EU)	080926-90338-8	90338
Bank Charger (SC) 120V AC (Knucklehead/Survivor LED)	080926-90400-2	90400
Bank Charger 12V DC (Knucklehead/Survivor LED)	080926-90401-9	90401
Bank Charger (SC) 230V AC (Survivor Series) (3 SLV)	080926-90403-3	90403
Knucklehead/Survivor LED alkaline battery pack (Batteries not included)	080926-90542-9	90542
Bank Charger (SC) 230V AC (Survivor Series)*	080926-90600-6	90600
Survivor (Low Profile) Smoke Cutter Plug Kit	N/A	908019

*Not shown



STREAMLIGHT



30 Eagleville Road • Eagleville, PA 19403 • 610-631-0600/800-523-7488 Phone • 610-631-0712/800-220-7007 Fax
www.streamlight.com ©Streamlight, Inc. Survivor 3/17