

FIRE FIGHTER BOOTS (HARVIK 9687)



PRODUCT NAME : FIRE FIGHTER BOOTS
PRODUCT CODE : MGFFG 0416
COLOR : BLACK & YELLOW

- Standard** : EN 345 (European Standard for Protective Boots for Fire fighters)
- Design Details** : Internal heel guard for easy on and off
 Insulated with open cell polymeric foam to guard against cold and heat
 Extra thick felt midsole provides protection against cold and heat
 Built-in cushioned insole provides all day comfort and eliminates foot discomfort
 Patented two piece stainless steel midsole provides greater arch support and protection against punctures
 Extra wide, heavy duty steel shank provides maximum arch support and comfort
 External rubber shin guard adds protection and comfort while working on ladders
- Type of construction** : Vulcanized Rubber Upper and Sole
- Lining Material** : Leg Lining : Woven Cotton Canvas
 Weight (min) 250g/m², Thickness (min) 0.60mm
 Insole Lining : Woven Sheeting
 Weight (min) 130g/m², Thickness (min) 0.30mm
- Rubber Components** : Upper : Black in Colour, 65% Natural Rubber, 30% Styrene Butadiene Rubber and 5% Chloroprene Rubber
- Foxing** : Yellow in Colour, 65% Natural Rubber, 30% Styrene Butadiene Rubber and 5% Chloroprene Rubber
- Outsole Pattern** : One piece Stainless Steel, Meets CSA-Z195-02 Sole Penetration and EN 345 Flexing test
- Steel Toe** : Meets EN 345 Impact and Compression
- Chemical Resistant** : Upper - Resistant towards mild acids and alkali Sole - Resistant towards mild acids
- Finishing** : Hypalon Lacquer
- Salient Features** : The features of firemen boots included felt lining and sturdy pull on loop.
 The steel toe and steel midsole exceed ANSI and OSHA requirements.
 High visibility white outersole and heels. Thick from insulation
 KEVLAR®/NOMEX® lining throughout which provides long gear and protection against punctures
- Sizes Availability** : 6,7,8,9 and 10

Performance Requirement :

Property	Test Standard
Electric Shock Resistant	Meets CSA-Z195-02
Resistance to Hot Contact	Meets both NFPA and EN 345-2
Energy absorption	Meets EN 345-2
Air Pressure	50kPa
Thickness of Upper and Fabric Combined	1.80mm (Minimum)
Weight	3.3 Kgs / Pair
Size	44