

## Respiratory protection

September 10, 2010 PGM-Head

## Product data sheet folding mask FFP2 with Carbon - uvex silv-Air 3220



## UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, 90766 Fürth, Germany

Product features	<ul> <li>Optimised shape</li> <li>Soft material edges for high wearing comfort</li> <li>The adjustable head band clips offer easy handling and comfortable fit</li> <li>Exhalation valve for reduced build-up of heat and moisture inside the mask</li> <li>Flexible and adjustable nose piece</li> <li>Mask fulfils the requirements of the dolomite dust test (D)</li> <li>Compatible with uvex safety eyewear</li> <li>Activated carbon filter for odours, gases and vapours below</li> </ul>	
	limit value	
Materials	Head band: elastic textile Nose piece: PP Headband clips: PP Filter / mask: Melt Blown PP, Polyester Sealing lip: EVA foam Valve: ABS	

Areas of use The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 10 times the respective limit values.	Mining, chemical industry, shipyards, iron and steel industry, woodworking, dust and fumes of substances such as asbestos, quartz, aluminium, copper, barium, titanium, vanadium, chrome, manganese and coal dust with more than 10% free silicon dioxide.
Weight	17g
Standard	EN 149:2001 + A1:2009

## **Versions/Colour:**

Artkle-No.	Colour/Version	Retail unit
8733.220	Folding mask FFP2, white with valve and	15 pieces per box
	carbon	